## INSTALLATION MANUAL OF CAR MAT SCREW FASTENING KIT

**If the product includes an additional set of floor screws, follow the steps below.**

1. Wear the personal protective equipment provided, such as safety goggles and safety gloves, to protect your eyes and hands.
2. Open the bag supplied with the mats, which contains a pin or screw to secure the mats to the floor of the car.
3. Place the mat in the intended position on the floor of the car. Make sure it fits properly and is securely positioned.
4. Using elements of the stopper holes as a guide, mark the locations on the floor where the fixing pins/screws will be inserted.
5. Screw the fixing pin/screw into the marked position, ensuring that it is securely fastened.



6. Press the stopper hole onto the fixed screw pin to secure the mat.
7. Enjoy your new mats.

Note: The manufacturer recommends that this procedure is carried out by a specialist workshop. We are not responsible for any damage caused to the vehicle floor as a result of self-installation of the kit.

## REPLACEMENT MANUAL FOR STOPPERS IN CAR MATS

**If the product includes an additional set of stoppers different from those already installed on the car mat, identify which type is compatible with your car – either the pre-installed stoppers or the additional stoppers provided to replace the mat's installation system. If replacement is required, follow the steps below.**

1. Wear the personal protective equipment provided, such as safety goggles and safety gloves, to protect your eyes and hands.
2. Open the bag supplied with the mats, which contains a different type of stopper.
3. Use a flat screwdriver to gently pry off the bottom of the stopper from the mat. Separate the top and bottom of the stopper and remove it completely, leaving a hole in the mat for the replacement stopper.
4. Insert the replacement stopper into the hole in the mat. Join the top and bottom of the stopper by pressing them firmly together.
5. Follow the diagrams in the installation manual to properly secure the mat to the car floor.
6. Enjoy your new mats.

GEYER & HOSAJA
rubber innovations

Producer: Geyer & Hosaja Sp. z o.o.,
Partynia 12, 39-310 Radomyśl Wielki, Poland
e-mail: gh_partynia@geyer-hosaja.com.pl

**IE**

When used as intended and in accordance with the manufacturer's instructions, the product is completely safe and presents no risk to users.

WARNING!
Use the product only as intended.
Modification of the product is strictly forbidden.
This product is not a toy.

Installation guide

Product safety sheet

Before installation and use, please read the enclosed product safety sheet and installation manual.

# PRODUCT SAFETY SHEET

INSTRUCTIONS FOR SAFE AND PROPER USE

**Rubber car mats**

Installation guide

Product safety sheet

**The manufacturer is not liable for any damage or accidents resulting from failure to follow or observe the installation manual!**

- Before fitting, cut off (with a knife or scissors) the hanger attached to the mat.
- Before fitting the mats in the car, remove previously used mats from the floorboard. These mats should be placed directly on the floorboard and not on top of other mats already in the car. Always clean the car floor thoroughly after removing old mats and before fitting new ones.
- For ease of installation, move the front seats as far back as possible when fitting the front mats.
- During installation, check the shape, position of the fasteners and manufacturer's labels on the mats to ensure that they are correctly positioned in their designated areas (for the driver, front passenger or rear row).
- After fitting the driver's mat, check that it does not interfere with the accelerator, brake or clutch pedals. The driver's and passenger's mats have a lowered edge so that they do not interfere with the accelerator or brake pedal.
- If your car has been washed or repaired, always check that the car mats are correctly fitted.
- If the mat comes loose or interferes with pedal operation, stop the car immediately in a safe place and reposition the mat or remove it if correct repositioning is not possible.
- The mats are not intended for performance, stunt or racing vehicles.
- Do not drive the car without footwear. Do not remove your shoes or place any objects on the floor while driving.
- On some models, the clips can be replaced or fitted to secure the mat to the floor.
- The mat can be trimmed to fit the specific floor contours of your car model. Use scissors to trim the mat at the manufacturer's marked position. Do not trim the mat unless the manufacturer has indicated this option on the mat (scissors symbol) or in the product documentation.
- Clean the mats regularly to prolong their life and improve comfort. Before cleaning, remove the mats and shake them outside the car.

### CLEANING AND MAINTENANCE

Rubber mats can be cleaned with a soft brush, sponge or pressure washer using standard mild detergents or chemical cleaners.

### QUALITY AND ENVIRONMENTAL CARE

Geyer & Hosaja car mats contain recycled materials, are PZH (National Institute of Hygiene at the National Institute for Public Health) certified, do not contain heavy metals and do not emit harmful substances.

**This product is 100% recyclable.**

Geyer & Hosaja is certified according to automotive standards: **ISO 9001:2015, IATF 16949** and **TÜV Rheinland.**

GEYER & HOSAJA
rubber innovations

Producer: Geyer & Hosaja Sp. z o.o.,
Partynia 12, 39-310 Radomyśl Wielki, Poland
e-mail: gh_partynia@geyer-hosaja.com.pl

Installation guide

Installation guide

Product safety sheet

WARNING!
Small parts
Keep out of the
reach of children.

IE

# INSTALLATION DIAGRAMS FOR GEYER & HOSAJA CAR MATS

| GH/I/1<br>GH/I/2<br>GH/I/3<br>GH/I/4<br>GH/I/5<br>GH/I/6 | GH/II/1<br>GH/II/2<br>GH/II/3<br>GH/II/4 | GH/III/1 | GH/IV/1<br>GH/IV/2 | GH/V/1 |
|---|---|---|---|---|
|  |  |  |  |  |
|  |  |  |  |  |
|  |  |  |  |  |
| | | |  |  |